

Threadlocker SELECTOR CHART

THREADLOCKERS



THREAD SEALANTS

PRODUCT	Low Strength Threadlocker PURPLE	Medium Strength Threadlocker BLUE	High Performance Thread Sealant	High Temperature Thread Sealant
SIZES PART NO	6 ml - #24024	10 ml - #24210 50 ml - #24250	50 ml - #56521	50 ml - #59235
COLOUR	Purple	Blue	White	White
FASTENERS/FITTINGS	2.2 - 6 mm	6 - 20mm	50mm	50mm
TORQUE, IN.-LABS	62/27	110/43	N/A	N/A
TEMPERATURE RANGE	-54°C to +149°C	-54°C to +149°C	-54°C to +149°C	-54°C to +204°C
APPLICATIONS	Carburetor relay locks, throttle body assembly, choke assembly, interior panel screws and fuel injection set screws	Rocker studs, rocker adjustment bolts, disc brake caliper bolts, intakes, alternator mounting bolts and pulley assemblies	Steel fittings, head bolts into through holes, oil PSI sending units/sensors, oils and coolant lines, intake manifold switches, rear axle fill plug, fuel fittings	Head bolts into through holes, oil PSI sending units/sensors, oil and coolant lines, fuel fittings, rear axle fill plug, brake/power steering fittings